

### SPECIFICATIONS

	Range	UT505A	UT505B	
Insulation resistance (Ω)	50V	50V/100V/250V/500V/1000V	0%~10%	0%~20%
		0.01MΩ~50MΩ	±(3%+5)	±(3%+3)
	100V	50MΩ~1GΩ		±(3%+3)
		1GΩ~10GΩ		±(10%+3)
		0.01MΩ~100MΩ	±(3%+5)	±(3%+3)
	250V	100MΩ~1GΩ		±(3%+3)
		1GΩ~20GΩ		±(10%+3)
		0.01MΩ~200MΩ	±(1.5%+5)	±(1.5%+5)
	500V	200MΩ~1GΩ		±(1.5%+5)
		1GΩ~50GΩ		±(10%+3)
		0.01MΩ~500MΩ	±(1.5%+5)	±(1.5%+5)
	1000V	500MΩ~1GΩ		±(1.5%+5)
1GΩ~100GΩ			±(10%+3)	
0.1MΩ~2000MΩ		±(1.5%+5)	±(1.5%+5)	
2GΩ~9.9GΩ		±(10%+3)	±(5%+3)	
Load current	10GΩ~20GΩ	±(20%+10)	±(7%+3)	
	20GΩ~200GΩ		±(20%+3)	
	50V (R=50kΩ) 1mA	0%~10%	0%~10%	
	100V (R=100kΩ) 1mA	0%~10%	0%~10%	
	250V (R=250kΩ) 1mA	0%~10%	0%~10%	
Short circuit current	500V (R=500kΩ) 1mA	0%~10%	0%~10%	
	1000V (R=1MΩ) 1mA	0%~10%	0%~10%	
Leakage current (A)	10~2000μA	<2mA	<2mA	
Low resistance (Ω)	0.01Ω~20kΩ (about 5V/>200mA)	±(1.5%+3)		
	0.01Ω~100Ω (about 5V/>200mA/20mA optional)		±(1.5%+3)	
General resistance (Ω)	0.01kΩ~10MΩ		±(3%+3)	
DC voltage (V)	0V~600V	±(2%+3)	±(2%+3)	
AC voltage (V)	0V~600V	±(2%+3)	±(1.5%+5)	
Frequency (Hz)	45~1kHz		±(0.1%+3)	
Capacitance (F)	100pF~500μF		±(5%+5)	
<b>Features</b>				
Display count		6000	6000	
Auto range/True RMS		√	√	
Step voltage	10% steps at 50%~120% of range	√	√	
DAR	60s/15s and 60s/30s	√	√	
PI/Timing measurement		√	√	
Auto discharge		√	√	
Auto fuse check			√	
Analog bar graph		√	√	
Continuity buzzer		√	√	
Comparison measurement		√	√	
Low battery indication		√	√	



● UT505A

UT505 series handheld true RMS insulation resistance testers combine features of a digital multimeter and insulation resistance tester. Aside from the typical multimeter functions, these meters can also measure insulation resistance, PI, DAR, and automatically calculate resistance ratio to determine the insulation status.

UT505 can be used in insulation resistance testing of precision tools, including motors, cables, transformers, switches, electrical appliances, and insulated materials.

- Auto power off
- LCD backlight
- High voltage output alarm
- 99-group data storage
- Data hold
- Meets IEC 61557 61557-1:2007; 61557-2:2007; 61557-4:2007

Váš distribútor:



**MERATEST s.r.o.**  
Družstevná 2, 916 01 Stará Turá  
Mobil: +421 903 533 859  
Tel.: +421 32/642 0909  
E-mail: molec@meratest.sk  
[www.meratest.sk](http://www.meratest.sk)

### GENERAL CHARACTERISTICS

Power	1.5V battery (LR6) x 6
Display	78mm x 59mm
Product color	Red and grey
Product net weight	630g
Product size	103mm x 225mm x 59mm
Standard accessories	Batteries, test leads, test probes, alligator clips
Standard individual packing	Carrying bag, gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	515mm x 380mm x 385mm (0.075 CBM per standard carton)
Standard carton gross weight	20.8kg
Optional accessory	Remote test lead