

# INSULATION RESISTANCE METER

## MIC-2501

**INSULATION  
RESISTANCE  
MEASUREMENT  
UP TO  
 $1\text{ T}\Omega$   
IN ACCORDANCE  
WITH IEC 61557-2**



- **Insulation resistance measurement:**

- selectable measurement voltage in the 100...2500 V range with 100 V step,
- continuous indication of insulation resistance or leakage current,
- automatic discharge of capacitance of tested object after the insulation resistance measurement,
- acoustic signalling of five-second periods to facilitate obtaining time characteristics,
- measured test times T1, T2 i T3 to measure one or two absorption coefficients in 15, 60 and 600 s,
- indication of actual test voltage during the measurement,
- protection against measuring live objects,
- two and three-lead measurement method,

- **Continuity measurement of protective and equipotential conductors according to EN 61557-4 with the >200 mA current.**

- **Leakage current measurement.**
- **Measurement of alternating and direct voltages in the 0...750 V range.**
- **Built-in rechargeable battery pack.**
- **The instruments meet the requirements of the EN 61557 standard.**
- **The ability to charge from car lighter (12 V) socket (additional accessories).**

**Obchodné zastúpenie v SR:**

**MERaTEST s.r.o.**

Družstevná 2  
(Dom štát. správy 2.p.)  
916 01 Stará Turá  
Tel.: 032/642 0909  
Mob.: 0903 533 859  
e-mail: [molec@meratest.sk](mailto:molec@meratest.sk)  
web: [www.meratest.sk](http://www.meratest.sk)

**Sonel S.A.**  
Wokulskiego 11  
58-100 Świdnica  
tel. +48 74 85 83 860  
fax +48 74 85 83 809

[export@sonel.pl](mailto:export@sonel.pl)  
[www.sonel.pl](http://www.sonel.pl)

# MIC-2501

## Insulation resistance measurement (two-lead)

Measurement range acc. to IEC 61557-2 for  $R_{ISOmin} = U_{ISOnom}/I_{ISOmax} \dots 1T\Omega (I_{ISOmax} = 1 \text{ mA})$

Range	Resolution	Accuracy
0.0...999.9 kΩ	0.1 kΩ	±(3% w.m. + 20 digits)
1.000...9.999 MΩ	0.001 MΩ	
10.00...99.99 MΩ	0.01 MΩ	
100.0...999.9 MΩ	0.1 MΩ	
1.000...9.999 GΩ	0.001 GΩ	
10.00...99.99 GΩ	0.01 GΩ	
100.0...999.9 GΩ	0.1 GΩ	

## Continuity measurement of protective connections and equipotential bonding with 200 mA current

Measurement range acc. to EN 61557-4: 0.10...999 Ω

Range	Resolution	Accuracy
0.00...19.99 Ω	0.01 Ω	±(2% w.m. + 3 digits)
20.0...199.9 Ω	0.1 Ω	
200...999 Ω	1 Ω	

- Voltage on open terminals: 4...24 V
- Output current at  $R < 2 \Omega$ :  $I_{sc} > 200 \text{ mA}$
- Compensation of test lead resistance
- Current flowing in both directions, mean value of resistance is displayed

Values of measured resistance depending on measurement voltage

Voltage $U_{ISO}$	Measurement range
500 V	500 GΩ
1000 V	1.00 TΩ
2500 V	1.00 TΩ

## DC and AC voltage measurement

Range	Resolution	Accuracy
0...299,9 V	0,1 V	±(3% w.m. + 2 digits)
300...750 V	1 V	±(3% w.m. + 2 digits)

- Frequency range : 45...65 Hz



### Electrical safety:

- type of insulation double, in acc. with EN 61010-1 and IEC 61557-2
- measurement category IV 600 V (III 1000 V) in acc. to EN 61010-1
- case protection rating in acc. with EN 60529 IP65

### Other technical specifications:

- |                                       |  |
|---------------------------------------|--|
| - power supply of the meter           | NiMH 9.6 V - 2 Ah battery pack and power supply 12 V |
| - weight of the meter                 | approx. 0.9 kg                                       |
| - dimensions                          | 200 x 180 x 77 mm                                    |
| - display                             | LCD segment display                                  |
| - measurement results memory          | 990 cells, 11880 records                             |
| - transmission of measurement results | USB  |

### Standard accessories:

- test lead banana plug; 1,8 m; 5 kV; red
- test lead banana plug; 1,8 m; 5 kV; blue
- test lead banana plug; 1,8 m; 5 kV; black
- USB cable
- "crocodile" clip 5,5 kV; black
- "crocodile" clip 5,5 kV; red
- "crocodile" clip 5,5 kV; blue
- pin probe 5 kV with banana connector; red
- pin probe 5 kV with banana connector; black
- carrying case
- power supply adaptor Z7
- meter harness
- DVD with software, including "SONEL Reader" (reading data from memory)
- calibration certificate
- warranty card

WAPRZ1X8REBB  
 WAPRZ1X8BUBB  
 WAPRZ1X8BLBB  
 WAPRZUSB  
 WAKROBL20K07  
 WAKRORE20K07  
 WAKROBU20K07  
 WASONRE0GB2  
 WASONBL0GB2  
 WAFUTM8  
 WAZASZ7

The acronym "m.v." stands for a "measured reference value".