

## UT701 Single Function Temperature Calibrator



- Up to 0.05% output accuracy
- 6 digit display
- Output functions: DC voltage, resistance, thermocouple, and thermal resistance
- 10 thermocouple scales
- 4 thermal resistance scales
- High precision automatic cold junction compensation for thermocouple outputs
- Manual stepping and automatic stepping and ramping
- Stores and recalls setups

### SPECIFICATIONS

	Type	Range	Accuracy
<b>Source accuracy</b>			
DC mV		100.000mV	±(0.05%+3)
		1000.0mV	±(0.05%+3)
Resistance (Ω)		500.0Ω	±(0.05%+2)
		5000Ω	±(0.05%+2)
Thermocouples	J	-20~1200°C (-328~2192°F)	±0.7°C
	K	-200~1370°C (-328~2498°F)	±1°C
	T	-200~400°C (-328~752°F)	±0.8°C
	E	-200~950°C (-328~1742°F)	±0.7°C
	R	-20~1750°C (-4~3182°F)	±1.4°C
	S	-20~1750°C (-4~3182°F)	±1.5°C
	B	600~1800°C (1112~3272°F)	±1.4°C
	N	-200~0~1300°C (-328~2372°F)	±0.9°C
	Wre325	0~2000°C (32~3632°F)	±1.8°C
	Wre526	0~2300°C (32~4172°F)	±1.8°C
RTDs	Pt10	-200~850°C (-328~1562°F)	±(0.5%+6°C)
	Pt100		±(0.05%+0.6°C)
	Cu50	-50~150°C (-58~302°F)	±(0.05%+0.6°C)
	Cu100		±(0.05%+0.6°C)
<b>Features</b>			
Ramp functions	Source functions: Voltage, resistance, temperature		
	Ramps: Slow ramp, Fast ramp, 25% step-ramp		
Step functions	Source functions: Voltage, resistance, temperature		
	Steps: 25% of range, 100% of range		



### GENERAL CHARACTERISTICS

Power	9V battery (6F22)
Display	63mm x 40mm
Product color	Red and grey
Product net weight	410g
Product size	96mm x 193mm x 47mm
Standard accessories	Test leads, battery
Standard individual packing	Gift box, English manual, cloth bag
Standard quantity per carton	5pcs
Standard carton measurement	325mm x 225mm x 285mm
Standard carton gross weight	4.5kg

Váš dodávateľ:

**MERATEST s.r.o.**

Družstevná 2, 916 01 Stará Turá

Mobil: +421 903 533 859

Tel.: +421 32/642 0909

E-mail: molec@meratest.sk

[www.meratest.sk](http://www.meratest.sk)