



CMP-2000

DIGITAL CLAMP-ON MULTIMETER

- AC current measurement (TRUE RMS) up to 1500 A and DC up to 2000 A.
- Measurement of INRUSH current in start-up phase of electrical device (high frequency of sampling).
- AC voltage measurement (TRUE RMS) up to 750 V and DC up to 1000 V.
- Resistance measurement and continuity test:
-continuity test with acoustic signalling (beeper) for resistance below 30 Ω.
- Capacitance measurement.
- Temperature measurement (Fahrenheit or Celsius).
- Frequency measurement.
- Duty cycle measurement.
- Diode test.



Standard accessories:

- test leads (2 pcs.)
- 9 V battery
- K type temperature probe

- case
- calibration certificate
- user manual

WAFUTLM3

Výhradný distribútor pre SR:

MERaTEST s.r.o.
Družstevná 2
(Dom štát. správy 2.p.)
916 01 Stará Turá
Tel.: 032/642 0909
Mob.: 0903 533 859
e-mail: molec@meratest.sk
web: www.meratest.sk

Sonel S.A.
Wokulskiego 11
58-100 Świdnica, PL
tel. +48 74 85 83 860
fax +48 74 85 83 809

export@sonel.pl
www.sonel.pl



CMP-2000

- AC current measurement (TRUE RMS) up to 1500 A and DC up to 2000 A.
- Measurement of INRUSH current in start-up phase of electrical device (high frequency of sampling).
- AC voltage measurement (TRUE RMS) up to 750 V and DC up to 1000 V.
- Resistance measurement and continuity test:
- continuity test with acoustic signalling (beeper) for resistance below 30 Ω.
- Capacitance measurement
- Temperature measurement (Fahrenheit or Celsius).
- Frequency measurement.
- Duty cycle measurement.
- Diode test.
- Additionally:
- safe, insulated measuring clamp,
- autoranging,
- „DATA HOLD“ function, for holding measured values,
- backlit LCD,
- „DC ZERO“ mode of measurement for DC current, possibility to zero the display and reading relative actual value less stored „zero“ value,
- „MAX/MIN“ function,
- over range indication,
- „AUTO-OFF“ function after 30min.

DC current measurement

Range	Resolution	Accuracy
0,0...659,9 A	0,1 A	±(2,0% m.v. + 5 digits)
660...2000 A	1 A	±(3,0% m.v. + 5 digits) for 660...1000 A ±(5,0% m.v. + 5 digits) for 1000...2000 A

AC current measurement (TRUE RMS)

Range	Resolution	Accuracy
0,0...659,9 A	0,1 A	±(2,0% m.v. + 10 digits) for 50...60 Hz ±(3,0% m.v. + 10 digits) for 61...400 Hz
660...1500 A	1 A	±(2,5% m.v. + 10 digits) for 50...60 Hz and 660...1000 A ±(3,5% m.v. + 10 digits) for 61...400 Hz and 660...1000 A ±(5,0% m.v. + 10 digits) for 50...400 Hz and 1000...1500 A

DC voltage measurement

Range	Resolution	Accuracy
0,000...6,599 V	0,001 V	
6,60...65,99 V	0,01 V	
66,0...659,9 V	0,1 V	
660...1000 V	1 V	

AC voltage measurement (true RMS)

Range	Resolution	Accuracy
0,000...6,599 V	0,001 V	
6,60...65,99 V	0,01 V	
66,0...659,9 V	0,1 V	
660...750 V	1 V	

Resistance measurement

Range	Resolution	Accuracy
0,0...659,9 Ω	0,1 Ω	
0,660...6,599 kΩ	0,001 kΩ	
6,60...65,99 kΩ	0,01 kΩ	±(1,0% m.v. + 5 digits)
66,0...659,9 kΩ	0,1 kΩ	
0,660...6,599 MΩ	0,001 MΩ	±(2,0% m.v. + 5 digits)
66,0...66,00 MΩ	0,01 MΩ	±(3,5% m.v. + 5 digits)

Capacitance measurement

Range	Resolution	Accuracy
0,0...6,599 nF	0,001 nF	±(3,0% m.v. + 30 digits)
6,60...65,99 nF	0,01 nF	±(3,0% m.v. + 10 digits)
66,0...559,9 nF	0,1 nF	±(3,0% m.v. + 30 digits)
6,600...59,999 μF	0,001 μF	
66,00...659,99 μF	0,01 μF	
660...659,999 μF	0,100 μF	
0,660...6,600 mF	0,001 mF	±(3,0% m.v. + 10 digits)

Frequency measurement

Range	Resolution	Accuracy
10...65,99 Hz	0,01 Hz	
66,0...659,9 Hz	0,1 Hz	
0,660...6,599 kHz	0,001 kHz	
6,60...65,99 kHz	0,01 kHz	
66,0...659,9 kHz	0,1 kHz	
0,660...1,000 MHz	0,001 MHz	

Temperature measurement

Range	Resolution	Accuracy
-20...0 °C		±(2,0% m.v. + 3 °C)
0...399 °C	1 °C	±(1,0% m.v. + 2 °C)
400...1000 °C		±(2,0% m.v. + 3 °C)
-4...31 °F		±(2,0% m.v. + 6 °F)
32..749 °F	1 °F	±(1,0% m.v. + 4 °F)
750...1832 °F		±(2,0% m.v. + 6 °F)

Duty cycle measurement

Range	Resolution	Accuracy
5...95%	0,1%	±(2,0% m.v. + 10 digits)

- frequency range: 40 Hz...20 kHz.

Electric security:

- measurement category
- protection class acc. to EN 60529

CAT IV 600 V acc. to EN 61010-1
IP30

Other technical data:

- power supply
 - display
 - continuity test
 - diode test
 - low battery indication
 - over range indication
 - temperature sensor
 - input impedance
 - AC bandwidth
 - auto power OFF
 - dimensions
 - weight
 - accordance with following standards
- 9 V battery type 6LR61
6600 counts, backlit LCD
threshold 30 Ω
test current of 0,8 mA , typical
open circuit voltage 3,2V DC, typical
BAT displayed
'OL' displayed
type K thermocouple
ca.10 MΩ (V DC i V AC)
50...500 Hz
30 minutes
281 x 108 x 53 mm
570 g (with battery)
EN 61010-1
EN 61010-2-032

Rated operational conditions:

- able to open the clamp:
 - operating temperature
 - storage temperature
 - operating altitude
- Ø 57 mm wire
70 x 18 mm bus bar
0...+50 °C
-20...+60 °C
max 2000m

Additional equipment of CMP-2000:

- AC line splitter (AC-16)

WAADAAC16

