



APPA A17

- 6,000 Count digital large scale display
- Analog Bar graph
- AC 100.0 Amps capability
- AC 0.001mA Resolution
- Auto Ranging
- Auto Hold
- Data Hold
- Peak Hold
- Comparator
- Low Pass Filter with high stability
- Auto Power Off (Disable)
- Up to 40mm dia. (750MCM) Conductor Size
- 4 feet Drop Proof
- Deluxe Carrying Case
- Hand Guard & Stream Line Designed
- Convenient Battery Door
- CAT. III 300V Safety Standard

Specifications:(All at 23°C ± 5°C < 80%RH)

AC A: Ranges: 6.000mA/60.00mA/600mA/6A/60A/100A

Basic Accuracy: ±(1.0%+3d)

Resolution: 0.001mA

General Specifications: Sampling Rate: 5 times/sec

Overloading Indication: "OL"

Low Battery Indication: 

Auto Power Off: Approx. 20 minutes

Operating Temperature: 0°C~50°C

Storage Temperature: -20°C~60°C

Temperature Coefficient: 0.2 x (Spec. Accuracy)/ °C, < 18°C, > 28°C

Maximum Conductor Size: Up to 40 mm dia. (750MCM) Conductor Size

Maximum Jaw Opening: Up to 43mm

Safety: IEC 61010 CAT III 300V and designed to meet UL61010 specifications

Battery Life: 60 hours (ALKALINE)

Power Requirement: 1.5V x 2pcs AAA Size batteries (IEC LR03)

Dimensions: 78mm(W) x 203mm(L) x 42mm(D)

Weight: Approx. 300g

Accessories: Carrying Case, Alkaline battery (installed) and manual.