

DT-9905/9908/9909



Features

- Display: 2.000 counts LCD display with function indication.
- Polarity: Automatic, (-) negative polarity indication.
- Overrange indication.
- Low battery indication.
- Auto power off: approx. 10 minutes.
- Measurement rate: 2 times per second, nominal.
- Data Hold (only DT-9909)
- Backlit Hold (only DT-9905, DT-9908)
- Logic Test (only DT-9909)
- Insulation: Class2, Double insulation.
- EN61010-1; CATII - 1000V.

Technical data

Function	Max. Range	Basic Accuracy	DT-9905	DT-9908	DT-9909
Voltage DC	1000V	±0,5%	*	*	*
Voltage AC	700V	±1,2%	*	*	*
Current DC	20A	±2,5%	*	*	*
Current AC	20A	±3,0%	*	*	*
Resistance	20MΩ	±1,0%	*	*	400 MΩ
Temperature	760°C / 1400°F	±3,0%		*	
Frequency	2000Hz	±1,5%		*	4000kHz
Capacitance	200μF	±4,0%	*	*	40μF
Diode Check			*	*	*
Continuity Test			*	*	*
Logic Test					*

Delivery: Test Leads, 9V Battery, Type-K temperature probe (DT-9908), Gift Box with carrying case



Váš distribútor:

MERATEST s.r.o., Družstevná 2 (Dom štát. správy 2.p.), 916 01 Stará Turá
 Mob.: **+421 903 533 859**, Tel.: +421 32 642 0909
 e-mail: molec@meratest.sk, web: www.meratest.sk