

Spec	Details
Operating Voltage	6V and 12V DC
Reverse Polarity Protection	Red LED Indication
Max Input Voltage	15VDC
Over Voltage Protection	Max 30VDC (10 sec.) with Red LED Indication
Battery Types	SLA (AGM), GEL & Flooded (WET)
Battery Sizes	6V (1.2Ah to 10Ah) and 12V (1.2Ah to 100Ah)
Ah Capacity Test	Simulated 20 hour (C20) load test to 10.50VDC
Ah Calibration	Calibrated at 0 (zero) position to brand new fully charged premium brand SLA batteries rated at C20 hour at 20°C (68°F)
Ah Result	Based on the battery under test temperature and state of charge
Adjustment Provides	± Ah adjustment to brand new fully charged standby SLA, cyclic GEL and car FLOODED lead acid batteries
Battery Table	Recharge or replace battery when Ah capacity available falls below 65% of the battery's stated capacity
Display Type	Blue Back-lit LCD
Flat Battery Warning	6V <5.30VDC, 12V <10.50VDC
Repeat Test Operation	Can perform repeat tests continuously
DCV Accuracy	±2% of displayed reading
Ah Accuracy	$\pm 5\%$ Fully charged premium brand C20 hour rated SLA batteries at 20 - 25°C (68 - 77°F)
Applied Pulsed Load	6A 1.2Ah - 7Ah, 18A 8Ah - 100Ah
Ah Calibration Adjustment	Approx. ±25 dgts
Case Construction	High impact ABS with holster
Dimensions	84(H) x 170(W) x 41(D)mm (including holster)
Warranty	12 months
IN THE BOX	ACT 612 Intelligent Battery Tester, ACT 612TL Test Leads, ACT 430N Soft Carry Case, Sample ACT BTL Labels, Operating Instructions and Certificate of Calibration

Váš dodávateľ:

MERATEST s.r.o., Družstevná 2 (Dom štát. správy 2.p.), 916 01 Stará Turá

Mob.: **+421 903 533 859**, Tel.: **+421** 32 642 0909 e-mail: **molec@meratest.sk**, web: **www.meratest.sk**